

SECTION A-A
BELL JOINT AT FLOOR
COST FOR WATERSTOP CONSIDERED INCIDENTAL TO THE PROJECT.




BELL JOINT AT FLOOR
COST FOR WATERSTOP CONSIDERED INCIDENTAL TO THE PROJECT.



PLAN VIEW - PHASE I (SHOWING PHASE I OF FLOOR BELL JOINT CONSTRUCTION )

NOTES:
TO CONSTRUCT THE FLOOR OF THE BELL JOINT WITH A PERMISSIBLE
CONSTRUCT THE FLOOR OF THE BELL JOINT WITH A PERMISSIBLE
CONSTRUCTION JOINT AS SHOWN.
REINFORCING STEEL WILL BE PLACED PRIOR TO PLACING THE PHASE I
CONCRETE.
THE COST OF THE WATERSTOP IS CONSIDERED INCIDENTAL TO THE PROJECT.
A 50 mm x 150 mm BEVELED KEYWAY WILL BE FORMED TO THE DISTANCE SHOWN
AND LOCATION NOTED BEFORE PLACING THE CONCRETE.
FOR DETAILS AND DIMENSIONS OF THE BELL JOINT REFER TO THE BELL
JOINT STANDARD SHEETS.



PLAN VIEW - PHASE II
(SHOWING PHASE II OF FLOOR BELL JOINT
AND BARREL FLOOR CONSTRUCTION )

STANDARD DESIGN

PERMISSIBLE CULVERT BELL JOINT

FOR

REINFORCED CONCRETE BOX CULVERTS
ALL SPANS

PROJECT DEVELOPMENT DIVISION
IOWA DEPARTMENT OF TRANSPORTATION

JAN. 2002

MCBJ 4-95

201 TOUR CUEET 100